BTC-70824-2

Multi Chemistry Battery Cap Charger
Battery Chargers



NSN: 6130-01-606-5295

Features

- Dedicated single-station charger that will charge the following batteries:
 - BB-2590/U (BT-70791A, BT-70791Bx or BT-70791Cx) in 5.5 hours*
 - BB-390B/U (BT-70790B) in 12 hours
 - BB-2557/U (BT-70757Bx) in 3 hours*
- Powered from 20 30 VDC, 50 W max, (or from 100 240 VAC using an optional AC power adaptor, or using an optional Solar Panel)**
- Equipped with a two-pin "trailer hitch" connector
- Simple solution for the user who does not require a bulk or multi-station charger

 * Higher capacity versions of the BB-2590/U and BB-2557/U are available and can be charged with slightly longer charge times.

** Input cables and solar panels are purchased separately



Related Products

BTA-70671	24 V DC NATO Input
BTA-70784	DC cable with Alligator Clips
BTA-70768	X90 Scavenger
BTP-591791-3	AC/DC Power Supply
BTP-70822-3G	Solar Panel, 62 W, Green
BTP-70822-3T	Solar Panel, 62 W, Tan
BTP-70227-T	Solar Panel, 124 W, Tan

Technical Specifications

Charger Dimensions	Length 84 mm
	Width 56 mm
	Height 51 mm
Cable Length	203 mm
Charger Security Strap Length	343 mm
Weight	0.17 kg
Operating Temperature	- 20°C to + 50°C
Storage Temperature	- 40°C to + 70°C
Material / Colour	Modified ABS Plastic / Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

June 202

All specifications are subject to change without notice

The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au www.eylex.com.au